


受控文件

鸣志电器(太仓)有限公司

MS17HD6L4200-48R

接线图
Wiring Diagram



励磁顺序VS. 旋转方向
Exciting Sequence vs. Direction of Rotation

STEP	A	B	C	D	CCW
1	+	+	-	-	
2	-	+	+	-	
3	-	-	+	+	
4	+	-	-	+	

从安装面看为顺时针方向
Clockwise view from mounting side

铭牌 Label Detail

XXXXXXXX-Work Order 加工单号
YY/MM/DD-Date Format 日期格式

MOONS' STEPPING MOTOR
TYPE MS17HD6L4200-48R
XXXXXXXX YY/MM/DD



矩阵式二维码
码制: Data Matrix

二维码内容: XXXXXXXX-XXXX
加工单号-流水号


混合式步进电机规格 Hybrid Stepping Motor Specifications

1. 相数 Number of Phase	2
2. 步距角 Step Angle	1.8°
3. 额定电压 Rated Voltage	2.6 V DC
4. 额定电流 Rated Current	2 Amp
5. 保持力矩 Holding Torque	0.63 Nm Typ. (Two phase on/rated current)
6. 相电阻 Phase Resistance	1.3 ohm $\pm$ 15% (20°C)
7. 相电感 Phase Inductance	2.9 mH $\pm$ 20% (1kHz 1V rms)
8. 转子惯量 Rotor Inertia	82 gcm ²
9. 电机重量 Motor Weight	0.39 kg
10. 绝缘等级 Insulation Class	B (130°C)


编码器 Encoder detail
型号 (Model): HN103-36B10
分辨率: 1000线

COLOR	WHT (白)	BLU (蓝)	GRN (绿)	ORG (橙)
SIGNAL	CH Z-	CH Z+	CH B-	CH B+
COLOR	YEL (黄)	BRN (棕)	RED (红)	BLK (黑)
SIGNAL	CH A-	CH A+	+Vcc	GND

编码器电缆线断面



电机电缆线断面



Unit:mm

第一角画法
First angle method

未注线性与角度尺寸公差
Tolerances for linear and angular dimensions
without individual tolerance indications
GB/T 1804-m eqv ISO 2768-1:m

未注形状与位置尺寸公差
Geometrical tolerance for features without
individual tolerance indications
GB/T 1184-K eqv ISO 2768-2:K

批准 Approve

标准化 Standardize

工艺 Process Review

审核 Check

设计 Design

This document is released for information only. Its reproduction in whole or in part or its dissemination to third parties is prohibited.
All trademarks and registered trademarks appearing on this document are the property of their respective owners.

Drawing No: 4611110043331 Rev. A3 SCALE: 1:1 Sheet 1 of 1